Technical data		
Display/User interface	Large four line display with blue back light 6-key user interface Logical menu structure	
Measurement parameters/ranges	pH Redox Temperature	0–9.99 0–999 mV 0–49.9 °C (only for Pool Relax oxygen)
Regulation	pH regulation (pH minus or pH plus optional) Redox (dosing of liquid chlorine)	
Modes of operation	Automatic, Manual, Off	
Monitoring and safety functions	Flow of measuring water cycle, separate power supply for dosing pumps, level of pH canister, level of disinfection canister	
Alarm functions	Measured value alarm. (Alarm thresholds are adjustable on both sides) Dosing time alarm Level alarm for fill level monitoring of the dosing container	
	· ·	level monitoring of the dosing container
Alarm relay	· ·	level monitoring of the dosing container
Alarm relay Dosing pumps	Level alarm for fill	level monitoring of the dosing container 1.5 l/h 3.0 l/h
	Level alarm for fill Potential-free pH and Redox:	1.5 l/h
Dosing pumps	Level alarm for fill Potential-free pH and Redox: Oxygen:	1.5 l/h
Dosing pumps Dosing counter-pressure	Level alarm for fill Potential-free pH and Redox: Oxygen: max. 1.3 bar max. 3 m	1.5 l/h
Dosing pumps Dosing counter-pressure Suction height	Potential-free pH and Redox: Oxygen: max. 1.3 bar max. 3 m PoolConnect – wire	1.5 l/h 3.0 l/h
Dosing pumps Dosing counter-pressure Suction height Communication	Potential-free pH and Redox: Oxygen: max. 1.3 bar max. 3 m PoolConnect – wire (optional)	1.5 I/h 3.0 I/h eless module for communication between Pool Relax and mobile phone via SMS
Dosing pumps Dosing counter-pressure Suction height Communication Protection class	Level alarm for fill Potential-free pH and Redox: Oxygen: max. 1.3 bar max. 3 m PoolConnect – wire (optional) IP 54	1.5 I/h 3.0 I/h eless module for communication between Pool Relax and mobile phone via SMS 0-240 V, 50/60 Hz

The connection and the commissioning of the Pool Relax is reserved for trained specialists!











Reliable technology with a new design. Made in Germany.

Crystal clear water with minimum effort – the Pool Relax demonstrates just how easy it is to achieve perfect water quality. The clearly structured menu and the large display provides simple and intuitive operation. The robust construction ensures reliable functionality. The Pool Relax sets new design standards: it is modern and elegant.







Relaxation guaranteed.

Safe water treatment

The Pool Relax ensures reliable and precise control of the set values relevant for optimal water treatment. The alarm function of the Pool Relax is activated in the event of fluctuations relating to the set values, or empty product containers, with acoustic and visual signals on the device.

Simple operation

Despite the various setting options, the Pool Relax is very easy to operate. All relevant functions are intuitive and can be set conveniently using the keyboard. The large four line display is clear and easy to read.

Flexibility

The Pool Relax is available in three care-options: chlorine, chlorine free using active oxygen or bromine. The treatment method of the Pool Relax can easily be converted at any time with minimum effort.

Optimised reliability

The use of high quality components combined with a sophisticated technical design ensures the Pool Relax carries out tasks reliably without disruption.