## **CLEAR VAC**

Pool Vacuum Kit




How to assemble your CLEAR VAC



Slide the SUCTION HEAD onto the lid of the MAIN BODY.



Insert the smaller end of the assembled POLES into the MAIN BODY and slide together until the grooved area is fully inserted.



Assemble the four POLES by fitting the smaller end of one POLE into the larger end of the next one. Slide together until the grooved areas are fully inserted.



Connect the HOSE onto the MAIN BODY and slide it as far as it will go.

## How to use your CLEAR VAC

Immerse the assembled CLEAR VAC and its HOSE into your above ground pool and let it fill with water until all air escapes.

IMPORTANT: Trapped air in your vacuum system may prevent the pump from operating correctly. In this case open the release valve of your pump and shake the hose until all air bubbles escape and only water drops out of your pump.



- 2. A. If you don have a wall skimmer: Switch off the pump and remove the cover of the water intoke of your above ground pool. Take the CONNECTORS included with your CLEAR VAC.

  and attach the correct one to the water intoke. Tighten by hand only.

  B. If you have a wall skimmer: Switch off the pump of your above ground pool. Take skimmer sho pen and of the HOSE and connect in onto the vacuum plate of your skimmer. Slide the HOSE on for a six will go, Skip slep 3 and confinee.
- the HOSE as for as it will go. Skip step 3 and confinue with step 4.

  3. Toke the open and of the HOSE and connect it onto connector at the water intake. Stide the HOSE as for as it will go.

  4. Switch on the pump of your pool and start using CLEARVAC to clean the bottom of your pool.

  5. Your CLEARVAC is made to vacuum debris from the ground of your above ground pool. The internal collecting bag is designed to trop feaves and larger debris, which could otherwise blog the filter of your pool. Make sure to empty this pre-filter regularly to ensure the maximum suction possible.

  5. However, the pool of the property of the pool of the property of th

How to empty the collecting bag of your CLEAR VAC

Turn the CLEAR VAC cap in anti-lock direction to open the cap



Take out the collecting bag, empty the collecting bag by cleaning leaves and debrits, then rinse it



After clearance bag, put the bag into the main body and slide the cap in clock direction



