

**NEW  
2017**



## GARDEN PAC INVERTER HEATPUMP SPECS

Model	GHD-150-0191	GHD-150-0185	GHD-150-0186	GHD-150-0188
Applied pool volume (m <sup>3</sup> )	20~40	30~60	40~75	65~120
Working air temp (°C)	-7 ~ 43			
Performance conditions: Air 26°C/Water 26°C/Humidity 80%				
Heating capacity (kW)	9.8	13.3	17.3	27.9
Heating capacity (kW) in silence mode	7.8	10.4	13.8	21.8
C.O.P	6.4~15.0	6.4~15.0	6.3~15.5	6.3~15.3
C.O.P in silence mode	7.4~15.0	7.4~15.0	7.3~15.2	7.3~15.3
Performance conditions: Air 15°C/Water 26°C/Humidity 70%				
Heating capacity (kW)	6.5	9.4	11.4	18
Heating capacity (kW) in silence mode	5.1	7.4	8.8	14.6
C.O.P	4.4~7.6	4.4~7.6	4.3~7.8	4.4~7.9
C.O.P in silence mode	5.1~7.6	5.1~7.6	5.2~7.8	5.1~7.9
Rated input power (kW)	1.4~0.2	2.1~0.25	2.6~0.33	4.0~0.58
Rated input current (A)	6.4~0.86	9.1~1.1	10.9~1.4	17.4~2.5
Power supply	230V/1Ph/50Hz			
Advised water flux (m <sup>3</sup> /h)	3~4	5~7	6.5~8.5	10~12
Sound pressure 1m dB(A)	39.3~48.0	42.8~52.1	44.2~52.9	48.6~55.5
Sound pressure 10m dB(A)	19.3~28.0	22.8~32.1	24.2~32.9	28.6~35.5
Water pipe in-out Spec (mm)	50			
Net Dimensions LxWxH (mm)	961x312x658	961x312x658	961x392x658	961x420x960
Net Weight (kg)	45	52	63	90

\* The advised pool volume indicated apply under following conditions:  
Swimming pool covered with insulated cover, System running at least 15 hours per day;  
Heating season from 15th October. If these conditions are not met, please kindly ask for professional advice.

\*\* Above data is subject to modification without notice for technical upgrade.