



SMG Series  
Gel-coat Sand Filter



Water for life and leisure



### Highlight Features:

- Suggested Installation: Domestic In-ground and pool
- Max operating pressure  
36 psi / 2.5 bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-0.8mm
- ABS lateral provided

### "SMG" Series Gel-Coat Filter

Gelcoat filter tank has been well-received by the industry due to the durability, trustworthy performance and smooth gelcoat fibreglass finish. With UV-resistant material used, it is able to operate under prolong sunlight for years of reliability. "SMG" Series side mount filters are equipped with a six-position, side mount multiport valve and ABS laterals.

#### FEATURES

- Non corrosive gel coat fibreglass tank
- Smooth finish
- Curved valve connecting elbow to reduce headloss
- Transparent lid provides clear view of filter media
- Air release valve
- 6 way multiport sidemount valve


#### Technical Information

Code	Model No	Filter Area(m <sup>2</sup> )	Valve Connections		Max Flow Rate		Sand(kg)
88014004	SMG500	0.20	1.5inch	50mm	167lpm	10.00m <sup>3</sup> /h	100
88014005	SMG650	0.33	1.5inch	50mm	275lpm	16.50m <sup>3</sup> /h	150
88014063	SMG750	0.44	2.0inch	63mm	369lpm	22.10m <sup>3</sup> /h	250
88014064	SMG900	0.64	2.0inch	63mm	531lpm	31.80m <sup>3</sup> /h	375

Note: Suggested sand weight varies with differences in filter media size. For reference only.

#### Product Dimension

Model No	A mm	B mm	C mm	D mm	E mm	F mm	G mm
SMG500	438	501	835	360	516	390	180
SMG650	453	516	926	380	666	390	180
SMG750	517	603	1023	440	770	500	220
SMG900	570	656	1163	480	920	780	220



Available from:



Waterpark & Aquarium / Competition Pool / Residential Pool / Commercial Pool / Water Treatment / Water Feature