

pentair filters



The original and still the industry standard. The patented GlasLok™ process creates a one-piece, fiberglass reinforced tank with UV resistant surface finish for years of unequalled strength and durability. This unique method locks in fiberglass preventing fibers from “blooming” under harsh conditions.

FEATURES

- 8 1/2" transparent closure with manual air-relief.
- Swing-away diffuser allows instant access to sand and all internal parts.
- Maximum operating pressure 3.5 bar.
- Maximum operating temperature 50°C Max.
- 10-year Tank Warranty.

Triton Side Mount with Multiport Valve & P.G.	19" TANK C/W 1.5" VALVE & PRESSURE GAUGE
	24" TANK C/W 1.5" VALVE & PRESSURE GAUGE
	30" TANK C/W 2" VALVE & PRESSURE GAUGE
	36" TANK C/W 2" VALVE & PRESSURE GAUGE

TECHNICAL SPECIFICATIONS					
Reference	Ø Filter		Flow Rate m³/h	Filter Area m²	Flange Conn.
	mm	Inch			
F-19S8-TRV	480	19"	8.5	0.17	1 1/2"
F-24S8-TRV	610	24"	14	0.29	1 1/2"
F-30S8-TRV	762	30"	22	0.45	2"
F-36S8-TRV	914	36"	32	0.54	2"



DIMENSIONS (mm)				
	F-19S8-TRV (TR40)	F-24S8-TRV (TR60)	F-30S8-TRV (TR100)	F-36S8-TRV (TR140)
A	825	955	1095	1200
B	400	400	610	610
C	480	610	762	914
D	242	242	292	292
E	110	110	150	150
F	70	70	70	70
G	463	530	590	657
H	524	592	671	738

FILLING WEIGHTS		
Reference	Sand Ø 0.4 - 0.8 mm	Gravel Ø 3 - 5 mm
F-19S8-TRV	52 kg	20 kg
F-24S8-TRV	108 kg	40 kg
F-30S8-TRV	200 kg	80 kg
F-36S8-TRV	310 kg	120 kg